

Rental power unit 4 kW SA 1694



- 4 kW
- Maximum flow rate
6.5 l/min
- Maximum pressure
180 bar



Technology of Switzerland

HAGENBUCH
Hydraulic Systems



Technical data

Max. flow rate	6.5 l/min
Max. pressure	180 bar
Return filter	10 micron
Manual pump	20ccm / double lift
Valve block	6-fold with 5 electro-directional valves and valve for de-pressurised circulation
Oil tank	40 litre
Dimension in mm (l x w x h)	700 x 500 x 1000
Weight	200 kg (without oil)

Electrical connections

1 x CEE-plug 16 A (400VAC / 50Hz), with cable l = 3.5m

Hydraulic connections

Pressure connections A-side	5x R3/8"
Pressure connections B-side	5x R3/8"

Special

- 6-fold valve block with 4 pcs. 4/3-directional valves and 1x 4/2 directional valve with valve for engaging pressure
- Pressure limiter valve on valve block
- Valves can lock in on and off position using rotary switch
- Slow motion possible with built-in manual pump
- Line fuse for electrical valve controls
- Pump can be activated and de-activated with rotary switch (main switch)
- Manometer to monitor pressure

Accessories / parts subject to wear

Replacement filter cartridge	1 piece (Art.-No. 63.0200.0310)
Filling and air vents	1 piece (Art.-No. 62.1073.6140)

202501/V03/E