


Rental power unit 30 kW SA 1882



- 30 kW
- Maximum flow rate
110 l/min at max. 165 bar
- Maximum pressure
240 bar at max. 75 l/min

HAGENBUCH
Hydraulic Systems



Technical Data

Max. flow rate	110 l/min at max. 165 bar
Max. pressure	240 bar at max. 75 l/min
Pump pressure control	Adjustable using adjusting screw
Pump flow rates	Adjustable using adjusting screw
Pressure filter	5 Micron
Return filter	10 Micron
Filter/cooler-circle	40 l/min, air cooler
Oil tank	320 litre
Return and tank connections	10 connections in different sizes
Fill level monitor	Alarm when the level is too low, automatically shuts off if level drops too low, automatically shut off by over-temperature
Dimensions in mm (L x w x h)	1750 x 1350 x 2000
Weight	750 kg (without oil)

Electrical connections

1 x CEE-plug 63 A (400VAC / 50Hz), with cable l= 5m

Hydraulic connections

Pressure connection	Ermeto 30 S
Return connection	Ermeto 42 L, on return filter
Tank connection	2 x R 1"
Tank connection	2 x R 1"
Tank connection	2 x R 1/2"
Tank connection	1 x R 3/8"
Tank connection	2 x R 1/4"

Special

- Axial piston pump with adjustment screw for adjusting the maximum pressure and for adjusting and/or limiting the piston displacement
- Depending on use and to prevent overload of electrical motor, the pump can be set in the range of 75 l/min/240 bar 110 l/min / 165 bar
- Fill level monitor with automatic cut-off
- Emergency stop-button on aggregate
- Pump and pressure can be activated and de-activated with buttons
- Various monitored functions shown on display:
 - Emergency off circuit
 - Level drops too low (alarm)
 - Level drops too low (cut-off)
 - Filter contamination (alarm)
 - Oil-temperature too high (cut-off)
 - Phase sequence for feed 400VAC
 - Fault soft starter

Accessories / parts subject to wear

Replacement filter cartridge

- Return filter 2 pieces (Art.-No.: SC.0104.0007)
- High pressure filter 1 piece (Art.-No.: FP.9024.2131)

Filling and air vents 1 piece (Art.-No.: 62.1073.6140)

202501/V03/E